

## Practical example: diffraction

Eugeniy E. Mikhailov

The College of William & Mary



Lecture 11

Notes

---

---

---

---

---

---

---

---

### Diffraction

According to Huygens' principle, every point on the mask is a secondary source. Thus, the electric field magnitude at a target is expressed through a known electric field at a mask.

$$E_{target}(\vec{r}) \sim \int \int_{mask} dx' dy' \frac{E_{mask}(x', y')}{|\vec{r} - \vec{r}'|} e^{ik|\vec{r} - \vec{r}'|}$$

We assumed that both the mask and the target are parallel to the  $x - y$  plane and that  $\vec{r} - \vec{r}'$  is mostly parallel to  $z$  axis. Here

- $\vec{r} = (x, y, z)$  is the radius vector pointing to the target point,
- $\vec{r}' = (x', y', z')$  is the radius vector pointing to the mask/source,
- $k = \frac{2\pi}{\lambda}$  is the magnitude of  $k$ -vector.

Notes

---

---

---

---

---

---

---

---

### Diffraction approximation via sum

$$E_{target}(\vec{r}) \sim \sum_i \sum_k \Delta x' \Delta y' \frac{E_{mask}(x'_i, y'_k)}{|\vec{r} - \vec{r}'|} e^{ik|\vec{r} - \vec{r}'|}$$

Here

$$\begin{aligned} \vec{r} &= x, y, z \\ \vec{r}' &= x'_i, y'_k, z' \\ \vec{k} &= \frac{2\pi}{\lambda} \end{aligned}$$

It is important that the integrated function does not oscillate wildly from one sample point to another sample point. So, we need  $\Delta x'$  and  $\Delta y' \ll \sqrt{L\lambda}$ , where  $L$  is distance between the mask and the target.

Notes

---

---

---

---

---

---

---


---

### Sample of diffraction

Let's consider a diffraction of light on a mask shown below.



- resolution  $1386 \times 600$  pixels
- physical size  $2.8 \times 1.2$  cm
- distance to the target 1.1 m



- resolution  $693 \times 200$  pixels,
- physical size  $3.0 \times 1.4$  cm
- wavelength  $\lambda = 670$  nm

Calculation time 6 and half hours at the 6 core AMD computer

Notes

---

---

---

---

---

---

---

---